

Yuasa Scheda Tecnica

Yuasa NP12-12 Industrial VRLA Battery

Specifiche tecniche

| | |
|--|------|
| Tensione Nominale (V) | 12 |
| Capacità alla scarica in 20 ore - 10.5V, 20°C (Ah) | 12 |
| Capacità alla scarica in 10 ore - 10.8V, 20°C (Ah) | 11.1 |

Dimensioni

| | |
|---------------------------|-----------|
| Lunghezza (mm) | 151 (±1) |
| Profondità (mm) | 98 (±1) |
| Altezza poli inclusi (mm) | 97.5 (±2) |
| Peso (kg) | 4.05 |

Tipologia dei terminali

| | |
|-------------------------|------|
| Faston - attacco rapido | 6.35 |
|-------------------------|------|

Range di temperatura d'esercizio

| | |
|---|---------------|
| Stoccaggio (con batteria carica al 100%) | -20°C a +60°C |
|---|---------------|

Stoccaggio

| | |
|---|---|
| Perdita di capacità per mese a 20°C (% aprox.) | 3 |
|---|---|

Materiale del contenitore

| | |
|----------|---------------|
| Standard | ABS (UL94:HB) |
|----------|---------------|

Tensione di carica

| | |
|--|-------------|
| Carica a tampone a 20°C (V/batt) | 13.65 (±1%) |
| Carica tampone a 20°C (V/el) | 2.275 (±1%) |
| Coefficiente di correzione carica di tampone per temperature 20°C (mV/°C/el) | -3 |
| Tensione di carica ciclica o a fondo a 20°C V/batt | 14.5 (±3%) |
| Tensione di carica ciclica o a fondo a 20°C V/el | 2.42 (±3%) |
| Coefficiente di correzione carica ciclica con temperature 20°C (mV/°C/el) | -4 |

Corrente di carica

| | |
|--|----------|
| Limite di corrente di carica a tampone | No limit |
| Limite di corrente di carica ciclica o a fondo | 3 |

Corrente massima di scarica

| | |
|-------------------|-----|
| per 1 secondo (A) | 360 |
| per 1 minuto (A) | 75 |

Corrente di corto circuito & resistenza interna

| | |
|---|-------|
| Resistenza interna secondo IEC 60896-21 (m-Ohm) | 44.39 |
| Corrente di corto circuito secondo IEC 60896-21 (A) | 320 |

Impedenza


| | |
|-------------------|----|
| Misurata ad 1 kHz | 18 |
|-------------------|----|

Vita progetto ed approvazioni

| | |
|--|-----------------|
| Classificazione Eurobat Standard Commercial" | 3 a 5 |
| Vita progetto Yuasa a 20°C (anni) | fino a 5 |
| VdS (Mercato tedesco) | VdS No: G189170 |



Layout



Certificazione di terze parti

ISO9001 - Sistema di gestione Qualità
UNDERWRITERS LABORATORIES Inc.



Sicurezza

Installazione

Può essere installata in ogni posizione eccetto permanentemente capovolta.

Maniglie

Se la batteria è provvista di maniglie , queste non possono essere utilizzate per installare le batterie sospese.

Valvole di ventilazione

Ogni singola cella è provvista di valvole a bassa pressione in grado di rilasciare gas in eccesso e richiudersi automaticamente.

Rilascio di gas

Le batterie VRLA possono rilasciare idrogeno, che può generare miscela esplosiva con l'aria. Non installare in contenitori ermetici.

Riciclaggio

Le batterie Yuasa devono essere riciclate a fine vita in accordo con le legislazioni e regolamentazioni locali.

Data di pubblicazione: 19/11/2015 - E&OE



Yuasa Technical Data Sheet



Yuasa NP12-12 Industrial VRLA Battery

Specifications

| | |
|---|------|
| Nominal voltage (V) | 12 |
| 20-hr rate Capacity to 10.5V at 20°C (Ah) | 12 |
| 10-hr rate Capacity to 10.8V at 20°C (Ah) | 11.1 |

Dimensions

| | |
|----------------------------|-----------|
| Length (mm) | 151 (±1) |
| Width (mm) | 98 (±1) |
| Height over terminals (mm) | 97.5 (±2) |
| Mass (kg) | 4.05 |

Terminal Type

| | |
|--|------|
| FASTON - Quickfit / release (JST where stated) | 6.35 |
|--|------|

Operating Temperature Range

| | |
|--------------------------------------|----------------|
| Storage (in fully charged condition) | -20°C to +60°C |
|--------------------------------------|----------------|

Storage

| | |
|---|---|
| Capacity loss per month at 20°C (% approx.) | 3 |
|---|---|

Case Material

| | |
|----------|---------------|
| Standard | ABS (UL94:HB) |
|----------|---------------|

Charge Voltage

| | |
|---|-------------|
| Float charge voltage at 20°C (V)/Block | 13.65 (±1%) |
| Float charge voltage at 20°C (V)/Cell | 2.275 (±1%) |
| Float Chg voltage tmp correction factor from std 20°C (mV) | -3 |
| Cyclic (or Boost) charge Voltage at 20°C (V)/Block | 14.5 (±3%) |
| Cyclic (or Boost) charge Voltage at 20°C (V)/Cell | 2.42 (±3%) |
| Cyclic Chg voltage tmp correction factor from std 20°C (mV) | -4 |

Charge Current

| | |
|--|----------|
| Float charge current limit (A) | No limit |
| Cyclic (or Boost) charge current limit (A) | 3 |

Maximum Discharge Current

| | |
|--------------|-----|
| 1 second (A) | 360 |
| 1 minute (A) | 75 |

Short-Circuit Current & Internal Resistance

| | |
|--|-------|
| Internal resistance - according to EN IEC 60896-21 (m) | 44.39 |
| Short-Circuit current - according to EN IEC 60896-21 (A) | 320 |

Impedance


| | |
|-------------------|----|
| Measured at 1 kHz | 18 |
|-------------------|----|

Design Life & Approvals

| | |
|---|-----------------|
| EUROBAT Classification: Standard Commercial | 3 to 5 |
| Yuasa design life at 20°C (yrs) | up to 5 |
| VdS (Germany) | VdS No: G189170 |



Layout



3rd Party Certifications

ISO9001 - Quality Management Systems
UNDERWRITERS LABORATORIES Inc.



Safety

Installation

Can be installed and operated in any orientation except permanently inverted.

Handles

Batteries must not be suspended by their handles (where fitted).

Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

